

 **MOFFETT-KOOI**

 **MOFFETT-KOOI**

M7

Moffett Engineering Limited
Ardee Road
Dundalk
County Louth
Ireland

Moffett-Kooi bv
Leijester Hegedyk 25
NL-9071 XB Oude Leije
Postbus 1
NL-9076 ZN St. Annaparochie
Netherlands

Tel: +353 (0)42 935 9500
Fax: +353 (0)42 935 9590
Email: info@moffett-kooi.com
Website: www.moffett-kooi.com



MOFFETT 099-999-0520



Delivering even **more**

PARTEK
Cargotec



Superb performance and reliability

The M7 is designed for a wide range of commercial and industrial applications. Offering high lift capacities, it is suitable for operation on paved surfaces and rough conditions. Distinguished by its user-friendly characteristics, the M7 gives supreme performance and reliability day in, day out.

Meeting the needs of your business

There is a model in the M7 range to meet almost every business need, which is why the range is already such a major success story in market sectors such as:

- Building materials
- Agriculture
- Animal foodstuffs
- Roofing
- Hardware
- Scaffolding
- Windows and doors
- The Emergency Services ...and many more!

Fully equipped as standard

Always expect the very best in standard equipment from your M7.

- Flashing beacon, reverse bleeper
- Work and road lights
- Safety door
- Seat belt
- Stabilisers

- Differential lock
- ROPS/FOPS (Rollover/Falling Object Protective Structure)

You always have an option

In addition to a comprehensive range of standard equipment, every M7 is designed to be flexible to incorporate a complete choice of customised options. These include:

- Choice of tyres
- Choice of forks
- Choice of three different lift heights
- Attachments

In harmony with your vehicle

Moffett-Kooi truck-mounted forklifts integrate easily and efficiently with your truck or trailer. They mount and dismount in less than 60 seconds – putting you in complete control of the collection and delivery process.



In less than 60 seconds the Moffett-Kooi forklift can mount or dismount a truck or trailer and be ready for work.



	24.3	27.3	30.3	35.3
1 LIFT CAPACITY	2400 KG @ 500 MM LOAD CENTRE	2700 KG @ 500 MM LOAD CENTRE	3000 KG @ 500 MM LOAD CENTRE	3500 KG @ 500 MM LOAD CENTRE
2 ENGINE	KUBOTA DIESEL 37.3 KW (50 HP)	KUBOTA DIESEL 37.3 KW (50 HP)	KUBOTA DIESEL 37.3 KW (50 HP)	KUBOTA DIESEL 37.3 KW (50 HP)
3 LIFT HEIGHT	3040 MM	3040 MM	3040 MM	3040 MM
4 STANDARD TYRES	27X10-12	27X10-12	27X10-12	27X10-12
5 DRIVE WHEELS	3 WHEEL	3 WHEEL	3 WHEEL	3 WHEEL
6 UNLADEN WEIGHT*	2425 KG	2505 KG	2700 KG	3050 KG
7 OVERHANG*	1450 MM	1450 MM	1450 MM	1450 MM
8 GROUND CLEARANCE	280 MM	280 MM	280 MM	280 MM

4-way models also carry loads sideways, ideal when delivering long loads into tight access areas or through narrow doorways.

	24.4	27.4	30.4	35.4
1 LIFT CAPACITY	2400 KG @ 500 MM LOAD CENTRE	2700 KG @ 500 MM LOAD CENTRE	3000 KG @ 500 MM LOAD CENTRE	3500 KG @ 500 MM LOAD CENTRE
2 ENGINE	KUBOTA DIESEL 37.3 KW (50 HP)	KUBOTA DIESEL 37.3 KW (50 HP)	KUBOTA DIESEL 37.3 KW (50 HP)	KUBOTA DIESEL 37.3 KW (50 HP)
3 LIFT HEIGHT	3040 MM	3040 MM	3040 MM	3040 MM
4 STANDARD TYRES	27X10-12	27X10-12	27X10-12	27X10-12
5 DRIVE WHEELS	3 WHEEL, 4-WAY	3 WHEEL, 4-WAY	3 WHEEL, 4-WAY	3 WHEEL, 4-WAY
6 UNLADEN WEIGHT*	2650 KG	2730 KG	2955 KG	3285 KG
7 OVERHANG*	1485 MM	1450 MM	1450 MM	1450 MM
8 GROUND CLEARANCE	280 MM	280 MM	280 MM	280 MM

The above specifications can be changed by the manufacturer without prior notice. *These figures will vary depending on machine specification and type of mounting kit.